


Description

The T216 is a Single-Mode Fiber (SM) based Fiber Bragg Grating (FBG) Surface Strain Sensor for use in environments from -20°C to +120°C with rugged 3mm OD cable pigtails.


Ready for direct mounting steel construction exhibiting excellent wavelength to strain linearity. Calibration service available upon request. The full-scale (FS) accuracy and precision specifications take into account any hysteresis, non-linearities, and the repeatability of the sensor. The T216 sensor handling and installation is fast, easy and intuitive. Delivers the advantages inherent to FBG based sensors. Immune to lightning and electromagnetic interference (EMI). T216 series Surface Strain Sensors are fabricated using licensed and proprietary state-of-the-art laser manufacturing technologies.




Manufactured and sold by Technica under International Licenses from Raytheon Technologies

Key Features

Strain and temperature linearity. The T216 strain sensor design uses one precision made FBGs written into the fibers' core for producing a transducer configuration of high linearity, resolution, accuracy, and precision. Multiple Reflectivity, SLSR, & BW options available.



Rugged packaging format. The T216 sensor is well suited for precisely measuring strains in outdoor applications and can be manufactured with ultra-low bend radius fiber for meeting the needs of even the most demanding fiber routing applications.



Pre-Strain level is set at the factory. The T216 pre-strain level can be factory set to accommodate any strain range within the strain limits of -2000 $\mu\epsilon$ to +7,000 $\mu\epsilon$.

Spot-welded. The T216 is designed to be surface mounted by spot-welding. Epoxy installation or securing with screws is also possible. Installation video available upon request.

Ready to be daisy chained and field proven. Well suited for projects that include the need to monitor strain at one or many locations. Provided as single connectorized sensors or in ready to install arrays of various lengths and with a flexible number of sensors. For projects requiring stable operation for the long-term.

Parameter	Specifications
Wavelengths and Tolerance	1460 to 1620 nm, +/-0.5 nm
Reflection BW (FWHM)	0.6 nm to 2.0 nm; other opt.
Reflectivity %	>70%, other options
SLSR	10 dB, 12 dB, 15 dB; other
Strain Range	- 2000 $\mu\epsilon$ to +7000 $\mu\epsilon$
Strain Sensitivity	1.2 $\mu\text{m}/\mu\epsilon$
Strain Precision	<0.05% FS (<0.02% FS typical)
Strain Accuracy	<0.25% FS (<0.1% FS typical)
Gage Length, Gage Factor	20mm, 0.808
Temperature Compensation	Not applicable (see T217)
Temperature Accuracy	Not applicable (see T217)
Sensor Pigtail (Length, DIA)	1 m, 3mm OD rugged cable
Cable Bend Radius	24 mm std; 10mm option
Optical Connector	FC/APC std, LC/APC option
Housing Material	Stainless Steel SUS304
In-Shell Dimensions (LxWxH) Sensor Dimensions (LxWxH)	96.8x28x7.35 mm 96.8x20x7.35 mm
Weight	22 grams
Mounting Methods	Spot Welding, Screws, Glue

Applications in Civil Engineering, Energy, Industrial, Medical, and Research Laboratories


Technica undertakes a rigorous development process before products release. The company is also firmly committed to continuous improvements after release to insure performance to the highest standards, hence, specifications are subject to update without notice.

Technica Optical Components / 3657 Peachtree Rd, Suite 10A, Atlanta, 30319, USA, info@technicasa.com, www.technicasa.com


Spot-welding is the primary recommended method for achieving a long term stable bond between the monitored structure and the T216 sensor. It takes 10 minutes.

Tools: (1) TS900 or equivalent spot welder for 0.2mm steel plates, (2) FBG interrogator


T216 Top View before Installation




T216 is secured with tape to the clean surface”



Spot welding of the sensor to the surface: The T216 is surrounded by an SS304 shell which enables spot-welding the sensor to the monitored structure. There are 8 spot-welds that need to be done in order to properly secure the T216 strain sensor to the target surface.



Pull-up / snap-off the shells from the T216 Sensor:



Spot Welder Note: We recommend using our TS900 Spot Welder, which has been optimized for Optical Sensing Applications. Other spot-welders may be compatible as well.

Installed T216 Strain Sensor:



Applications in Civil Engineering, Energy, Industrial, Medical and Research Laboratories

Technica undertakes a rigorous development process before products release. The company is also firmly committed to continuous improvements after release to insure performance to the highest standards, hence, specifications are subject to update without notice.

Technica Optical Components / 3657 Peachtree Rd, Suite 10A, Atlanta, 30319, USA, info@technicasa.com, www.technicasa.com